

LOAD CELLS

* C6 on request

Modele	F60X	SK30X	ZFA	ZA30X	R10X	RH10X	CB50X	CA40X
Type	Bending beam		Tension		Compression			
Rated load capacity (C.N.)	5 kg ... 5 t	300 kg ... 5 t	25 kg ... 5 t	0.5 t ... 7.5 t	1 t ... 100 t	100 t ... 1 000 t	5 t ... 60 t	100 t ... 200 t
Accuracy class	C3*	C3*	-	C3	-	-	C4	-
Combined error (% C.N.)	0.017	0.017	0.03	0.017	0.1	0.2	0.013	0.024
Construction	Stainless steel	Stainless steel	Nickel plated steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Protection	Sealed, IP68	Sealed, IP68	Coated, IP65	Sealed, IP68	Sealed, IP68	Sealed, IP68	Sealed, IP68	Sealed, IP68
Certifications	OIML, ATEX, FM	OIML, NTEP, ATEX, FM	-	OIML, ATEX	ATEX, FM	ATEX	OIML, ATEX, FM	ATEX, FM

ELECTRONICS

● : Standard
○ : Optional

Modele	CPJ	eNod4	eNod3	PAX-S	IPE50 Panel	IPE50 Din	IPC50
Type	Weighing transmitters			Weighing indicators			
Accuracy class	0.05 %	0.005 %	0.005 %	0.02 %	0.005 %	0.005 %	0.005 %
Internal resolution	-	24 bits	24 bits	16 bits	24 bits	24 bits	24 bits
Formatted resolution	-	±500 000 pts	±500 000 pts	100 000 pts	200 000 pts	200 000 pts	200 000 pts
Max. measuring speed	-	6.25 ... 1 600 meas./s.	6.25 ... 1 600 meas./s.	20 meas./s.	200 meas./s.	200 meas./s.	100 meas./s.
Logic Input (I) / Output (O)	○ 2 S	● / ● 2 E / 4 S	● / ● 2 E / 2 S	● / ○ 2 E / 2 S	● / ○ 2 E - 2 S / 6 S	● 2 I / 2 ○	○ 2 I / 2 ○
Analog output	0 - 10 V 4 - 20 mA	-	-	0 - 10 V 4 - 20 mA	0 - 10 V 4 - 20 mA	0 - 10 V 4 - 20 mA	0 - 10 V 4 - 20 mA
Communication	-	USB/RS485/ CANbus	RS232/RS485/ CANbus	RS232/RS485	RS232/RS485	RS232/RS485	RS232/RS485
Construction	ABS Box	DIN Rail Box	Aluminum box	ABS Panel	ABS Panel	ABS Housing	ABS Housing
Protocols	-	MODBUS PROFIBUS CANopen®	MODBUS CANopen®	MODBUS PROFIBUS	MODBUS PROFIBUS ASCII	MODBUS PROFIBUS ASCII	ASCII
Protections	-	-	IP67	IP65 front panel	IP65 front panel	IP65 front panel	IP65 front panel
Display	-	-	-	LED 14 mm	LED 18 mm	LED 9 mm	LCD 25 mm
Certifications	-	-	OIML 6 000 d	-	OIML 10 000 d	OIML 10 000 d	OIML 10 000 d



Control Industrial Process

Vessel Weighing, Level Control



Technosite Altéa - BP501 - F 74105 ANNEMASSE Cedex
Tél. : +33 (0)4 50 87 78 64 - Fax : +33 (0)4 50 87 78 46 - info@scaime.com

Download all our technical documents from our website:

www.scaime.com

FA-Process/Indus-E-0212 - SCAIME - SIREN 389 325 283 - R.C.S. THONON LES BAINS - SIRET 389 325 283 00015 - SCAIME reserves the right to bring any modification without prior notice - All rights reserved.

Your process under control...

Reliability and safety are the most important factors to be taken into account when it comes to installing tank or silo weighing system. Scaime has designed solutions to meet these requirements in all circumstances.

WEIGHING SOLUTION


Load cells:

To fulfil each of your needs, our load cells cover a wide range of measuring capacities and are offered with different levels of protection and accuracy classes.


Mounting kits:

In order to restrict the influence of the environment on the performance of your measuring chain, we offer a wide range of accessories and mounting kits, suited to each application.

Hopper and blender weighing:




Tank and silo weighing:



Horizontal tank weighing...

For level measurement of a lesser accuracy in tanks filled with liquids, it is possible to replace 2 of the 4 load cells with fixed bearings.



ATEX

Measuring chain :

Scaime offers all of the elements allowing a weighing system, adapted to your needs, to be built.


For a better integration into industrial environments, we offer:








- solutions for weighing in potentially explosive atmospheres.
- standardized interfaces to the main automation systems (Profibus DP, Modbus-RTU...)

ATEX Certificats:

You will benefit from SCAIME expertise in the field of measurement in potentially explosive atmosphere thanks to Systex, a flexible solution for any ATEX complying weighing installation. (LCIE certification)

Hanging hopper weighing:



	Mounting kits	for	5 kg	50 kg	500 kg	5 t	50 t	500 t	
	RUBBERKIT	F60X 200 kg						Compression mounting kit Elastomer compensating for misalignments
	ISOFLEX	SK30X SK30A		300 kg 		5 t			Compression mounting kit Vibration damping elastomer
	STABIFLEX	F60X SK30X SK30A				5 t			Compression mounting kit Built-in side stoppers and lift-off prevention High precision ball and cup decoupling
	SILOKIT-R	R10X			1 t 	30 t			Compression mounting kit Built-in lift-off prevention and jack screw Side stabilization prevention
	SILOSAFE	R10X			1 t 	100 t			Compression mounting kit Built-in lift-off prevention device and Rod end ball side stabilization of very high capacity
	STABICAN	CB50X CA40X				5 t 	200 t		Compression mounting kit Rod end ball side stabilization Built-in lift-off prevention device
	PLAQUE	RH10X					100 t 	1 000 t	High capacity load cell Compression mounting cups
	ROTULES	ZF ZA30X	25 kg 			7.5 t			Rod end ball joint kit Hanging hopper weighing