



Data Sheet 1530615


Product: 1054 UPT stikk PH
El-number: 1530615
Mat.no: EKO04320
EAN: 7020160432018
Packing: 5
Color: Polarwhite




Product description: Splashproof single socket outlet surface mounted. Delivered with lid and shutters. The socket outlet must be installed with the hinges in the top. Membranes must be punctured with cable, to maintain IP44. Classification: IP44 (The lowest IP degree must be considered when combinations of plug and socket outlets are in use)

Technical specifications: IP44 Single socketoutlet surface mounted.
With earth
Voltage: 16A / 250VAC.
Delivered with shutters
Mounting: Surface mounting
Color: Polarwhite.
Halogenfree.
Degree of protection: IP44 (The lowest IP degree must be considered when combinations of plug and socket outlets are in use)
Screw terminals
Maximum torque: 1,2Nm (According to IEC 62196-1)
Maximum cross section: 4mm²
Corrosion protected

Size



Wiring diagram



ELKO AS

E-mail: elko@elko.no
Internet: www.elko.no
Bank: 6219.05.15880
Org.no.: NO 911 382 563 MVA

ELKO Front office
Sandstuveien 68, NO-0680 Oslo
P.O.Box 6598 Etterstad, NO-0607 Oslo
Tel.: +47 67 80 73 00
Fax: +47 67 80 73 01

ELKO Plant
Sporpind Industriområde, NO-3340 Åmot
Tel.: +47 32 78 91 00
Fax: +47 32 78 91 01