

## 17 Plyshield EPR Shielding Tape

### FOR SHIELDING HIGH VOLTAGE SPLICES AND TERMINATIONS

- Self-amalgamating
- Good conducting properties
- Easy to apply
- UV resistant

**RECOMMENDED USES:** For electro-static shielding on high voltage splices and terminations. Filling indents in compression connectors and rebuilding strand shielding on high voltage splices. Shielding bus and overhead connections.

#### STANDARD SIZES:

- 3/4 in x 15 ft.  
19mm x 4.6m

Consult factory for other sizes.

**DESCRIPTION:** 17 Plyshield is an ethylene propylene rubber based, self amalgamating and conducting tape. Its unsupported construction makes it ideal for use on power cable where accommodation of expansion and contraction due to load cycling is important. The excellent stretch of 17 Plyshield allows conformability to complex shapes. 17 Plyshield is compatible with all extruded dielectric cable insulations.

#### SPECIFICATIONS:

Property	Value	Unit	Test Method
<b>Physical</b>			
Color	Black	---	---
Thickness	0,76	mm	ASTM D 4325
	0.030	inch	ASTM D 4325
Tensile Strength	100 Min.	lb/in	ASTM D 4325
	175	N/cm	ASTM D 4325
Elongation	300	%	ASTM D 4325
Fusion	2 Max.	mm	ASTM D 4325
	5/64 Max.	inch	ASTM D 4325
<b>Operating Temperature</b>			
Continuous	90	°C	ASTM D 4388
Emergency Overload	130	°C	ASTM D 4388
<b>Chemical</b>			
Water Absorption	0,02	%	ASTM D 570
UV Resistance	Pass	Visual	ASTM D 4325
<b>Electrical</b>			
Volume Resistivity			
96 h @ 23 °C and 50 % RH	870	ohm · cm	ASTM D 4325
168 h @ 90 °C	5x10 <sup>4</sup>	ohm · cm	ASTM D 4325

Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use.

**LIMITED WARRANTY:** Plymouth warrants that its Product will substantially conform to that products written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment, (Unless provided otherwise in product's data sheet). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products.

