



Premium 37

Professional Grade Color Coding Vinyl Electrical Tape

DESCRIPTION:

A 7 mil (0,18 mm) all weather, professional grade, pressure sensitive vinyl tape that is available in nine colors for color coding and insulating. Cold and weather resistant. Flame retardant. Use Premium 37 for quick identification of electrical circuits, containers, and conduit systems, as well as primary insulation for splices at not more than 600 volts.

TECHNICAL CHARACTERISTICS

PROPERTY	VALUE	UNIT	TEST METHOD	
Thickness	0.007	inch	ASTM D 1000	
	0,18	mm	ASTM D 1000	
Tensile Strength	17	lb/in	ASTM D 1000	
	30	N/cm	ASTM D 1000	
Elongation	200	%	ASTM D 1000	
Adhesion to Steel	20	oz/in	ASTM D 1000	
	2,2	N/cm	ASTM D 1000	
Adhesion to Backing	20	oz/in	ASTM D 1000	
	2,2	N/cm	ASTM D 1000	
Adhesion to Backing @ -7°C	50	oz/in	ASTM D 1000	
	5,5	N/cm	ASTM D 1000	
Unwind @ 7°C	100	oz/in	ASTM D 1000	
	11	N/cm	ASTM D 1000	
Flammability	4 Max.	second	ASTM D 1000	
Flagging	0.12 Max.	inch	ASTM D 1000	
	2,5 Max.	mm	ASTM D 1000	
Temperature Rating Maximum	80	°C	UL 510	
	105	°C	CSA 22.2 no. 197	
Minimum	-10	°C	UL 510	
	-18	°C	CSA 22.2 no. 197	
Dielectric Strength	- Standard	7500	V	ASTM D 1000
	- Wet	6800	V	ASTM D 1000
Dielectric Constant	3.2	- - -	ASTM D 150	
Power Factor	0.01	- - -	ASTM D 150	
Insulation Resistance	1x10 ⁶	MΩ	ASTM D 1000	

Information provided is for reference only. Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use.

Revised March 2013

COLORS

- Red • Blue • Orange • Brown • Green
- White • Yellow • Violet • Grey

FEATURES:

- 7 mil thickness
- Cold and weather resistant
- High dielectric strength
- Highly elastic
- Highly conformable
- High UV resistance
- Flame retardant
- Highly resistant to sun, water, oil, acids, alkalis, corrosive chemicals
- Lead free
- Meets:
 - ASTM D 3005, Type I
 - ASTM D 1000
 - HH-1595C / A-A-55809A
 - EN 60454-3-1, Type 11
 - UL 510
 - CSA C 22.2 no. 197

RECOMMENDED USES:

Quick identification of electrical phases, circuits, feeders and branches. Also can be used to identify container contents, marking of piping and conduit systems and as a warning tape. Primary insulation for splices up to 600 volts. Can be applied at low temperatures.

STANDARD SIZES:

- 0.75 in x 66 ft
- 19 mm x 20 m

Other sizes are available upon request



LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment, (Unless provided otherwise in product's data sheet). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first compiled with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (rev. 1/95)